Express Mail Label No. EL915360557US

FÖRM PTO (REV. 11-2		ATTORNEY 'S DOCKET NUMBER
•	ΓRANSMITTAL LETTER TO THE UNITED STATES	2085-00200
-	DESIGNATED/ELECTED OFFICE (DO/EO/US)	U.S APPLICATION NO. (If known; see 37 CFR 1.5
	CONCERNING A FILING UNDER 35 U.S.C. 371	109 4:937.634
	NATIONAL APPLICATION NO. INTERNATIONAL FILING DATE	PRIORITY DATE CLAIMED
	G99/00020 22 March 1999	22 March 1999
	OF INVENTION IOD AND APPARATUS FOR ENCRYPTING AND DECRYPTING DATA	
	CANT(S) FOR DO/EO/US BAO et al.	
	ant herewith submits to the United States Designated/Elected Office (DO/EO/US)) the following items and other information:
1. 🗸	This is a FIRST submission of items concerning a filing under 35 U.S.C. 371.	
2.	This is a SECOND or SUBSEQUENT submission of items concerning a filing	under 35 U.S.C. 371.
3. 🔽	This is an express request to begin national examination procedures (35 U.S.C. 3 items (5), (6), (9) and (21) indicated below. (English translation not necessary a	371(f)). The submission must include as it was originally filed in English.)
	The US has been elected by the expiration of 19 months from the priority date (A	Article 31).
5. V	A copy of the International Application as filed (35 U.S.C. 371(c)(2))	1 Dungay)
	 a. is attached hereto (required only if not communicated by the Internation b. has been communicated by the International Bureau. 	onai Bureau).
T.	c. is not required, as the application was filed in the United States Receiv	ving Office (RO/US).
248	An English language translation of the International Application as filed (35 U.S	, ,
	a. is attached hereto.	
# # # # # # # # # # # # # # # # # # #	b. has been previously submitted under 35 U.S.C. 154(d)(4).	
7	Amendments to the claims of the International Aplication under PCT Article 19	
24.07 10.07 10.07	a. are attached hereto (required only if not communicated by the Internat	tional Bureau).
₽ ÿs∺	b. have been communicated by the International Bureau.	
	c. have not been made; however, the time limit for making such amendm	nents has NOT expired.
	d. have not been made and will not be made.	
8.	An English language translation of the amendments to the claims under PCT Art	ticle 19 (35 U.S.C. 371 (c)(3)).
	An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).	
10.	An English lanugage translation of the annexes of the International Preliminary Article 36 (35 U.S.C. 371(c)(5)).	Examination Report under PCT
Iten	ns 11 to 20 below concern document(s) or information included:	
11.	An Information Disclosure Statement under 37 CFR 1.97 and 1.98.	
12. 🔽	An assignment document for recording. A separate cover sheet in compliance	e with 37 CFR 3.28 and 3.31 is included.
13.	A FIRST preliminary amendment.	
14. 🔲	A SECOND or SUBSEQUENT preliminary amendment.	
15.	A substitute specification.	
16. 🗸	A change of power of attorney and/or address letter.	*
17. 🔲	A computer-readable form of the sequence listing in accordance with PCT Rul	le 13ter.2 and 35 U.S.C. 1.821 - 1.825.
18.	A second copy of the published international application under 35 U.S.C. 154((d)(4).
19. 🔲	A second copy of the English language translation of the international applicat	tion under 35 U.S.C. 154(d)(4).
20. 🗸	Other items or information: International Application as published (cover sheet only); PCT Form PCT/IPE Form; International Search Report; and an acknowledgment postcard.	EA/402; Form PCT/IB/308; PCT Request

JC09 Rec'd PCT/P10 2 4 SEP 200'

U.S. APPLICATION NO. (JEKNOS NOT YEZASSEN	s. APPLICATION NO. (FERDAND, 20, 37 FFR 16) INTERNATIONAL APPLICATION NO PCT/SG99/00020					ATTORNEY'S DOCI 2085-00200	
21. The following fees are submitted:						LCULATIONS	PTO USE ONLY
BASIC NATIONAL	_			· · · ·			
Neither internation	al preliminary ex						
nor international se and International S	arch fee (37 CFR earch Report not	1.445(a prepared	(2)) paid to USPTO by the EPO or JPO	\$1000.00			
International prelin USPTO but Interna	ninary examinationational Search Re	on fee (3 port pre	7 CFR 1.482) not paid to pared by the EPO or JPO	\$860.00			
International prelin but international se	ninary examinatio arch fee (37 CFR	n fee (3 1.445(a	7 CFR 1.482) not paid to (2) paid to USPTO	USPTO \$710.00			
International prelin but all claims did n	ninary examination ot satisfy provision	on fee (3° ons of P(7 CFR 1.482) paid to US CT Article 33(1)-(4)	PTO \$690.00			
International prelin	ninary examinatio	n fee (3	7 CFR 1.482) paid to US	РТО			
	•		rticle 33(1)-(4)			000.00	
ENTE	R APPROPR	IAIE	BASIC FEE AMO	UNI =	\$ 1	,000.00	
Surcharge of \$130.0 months from the earl	0 for furnishing the first claimed prior	he oath ority date	or declaration later than (37 CFR 1.492(e)).	□ 20 □ 30	\$		
CLAIMS	NUMBER FIL	ED	NUMBER EXTRA	RATE	\$		
Total claims	46 - 20		26	x \$18.00	\$	468.00	
Independent claims	4 -3		1	x \$80.00	\$	80.00	
MULTIPLE DEPEN				+ \$270.00	\$	00.00	
100.00			F ABOVE CALCU		\$	1,548.00	
Applicant claim are reduced by	is small entity sta 1/2.	tus. See	37 CFR 1.27. The fees	indicated above +	\$	774.00	
				JBTOTAL =	\$	774.00	
Processing fee of \$1 months from the ear	30.00 for furnish liest claimed prio	ing the E rity date	English translation later to (37 CFR 1.492(f)).	nan 20 30	\$	00.00	
			TOTAL NATIO	NAL FEE =	\$	774.00	
Fee for recording the accompanied by an	e enclosed assign appropriate cover	ment (37 sheet (3	7 CFR 1.21(h)). The assi 37 CFR 3.28, 3.31). \$40.	gnment must be 00 per property +	\$	40.00	
I.J.			TOTAL FEES E	NCLOSED =	\$	814.00	
## 11 m						ount to be refunded:	\$
in the			*		<u> </u>	charged:	\$ 814.00
a	the emerge of	`	to cover the	1 <i>C</i>	1	<u> </u>	
a. A check in	the amount of	·	to cover tr	e above fees is enclos	sea.		
b. Please char A duplicate	ge my Deposit A copy of this she	ccount Net is enc	No. <u>03-2769</u> in losed.	the amount of $$ 81^2$	4.00	to cover the	above fees.
			ized to charge any addition				ny
			o. <u>03-2769</u> . A duplic				
			d. WARNING: Inform d on this form. Provide				
-							3
			under 37 CFR 1.494 or to restore the application			petition to revi	e (37 CFR
SEND ALL CORRESPO	ONDENCE TO:				سندث	14. 11	
Jonathan M. Harris				SONATT.	10 E	· No va	4
CONLEY, ROSE				MGNATO	NE	**	
P.O. Box 3267 Houston, Texas 77	7253-3267			Jonatha	an M.	Harris	
United States of A			•	NAME			
DATE: Cambanala	- 24 2001			Reg. N			
DATE: September	24, 2001			REGISTR	AHON	NUMBER	*

JC09 Rec'd PCT/PTO 2 4 SEP 2001

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants:

Feng BAO et al.

\$ \$ \$ \$

Serial No.:

Not Yet Assigned

Group Art Unit:

UNKNOWN

Filed:

Concurrently Herewith

Examiner:

UNKNOWN

For:

Method And Apparatus For

Express Mail Label No. EL915360557US

Encrypting And Decrypting Data §

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents Washington, D.C. 20231

Att'y. Docket No. 2085-00200 Client Ref. No. KRD-P004US(WO) Date: September 24, 2001

Sir:

This paper is filed concurrently with the National Phase Entry patent application.

Prior to examining this case, the Examiner is requested to enter the following amendments and consider the accompanying remarks.

IN THE CLAIMS:

Please amend claims 4, 5, 8, 11-13, 17, 20-23, 27, 28, 31, 34-36, 40, and 43-46 by replacement with the following rewritten claims. A marked up version of the amended claims, showing the changes by underlining of the added text and bracketing of the deleted text, is appended hereto.

- 1 4. A method according to claim 1 wherein step (e) includes outputting the size of the
- 2 corresponding data segment.
- 1 5. A method according to claim 1 wherein said first function includes a cryptographic
- 2 pseudo random generator.

- 1 8. A method according to claim 1 wherein said accessory data strings are derived
- 2 from various sources.
- 1 11. A method according to claim 1 wherein said second function includes an
- 2 encryption function of a symmetric key cipher.
- 1 12. A method according to claim 1 wherein said second function includes an
- 2 encryption function of a block cipher operating in a well known mode, such as Electronic
- 3 Code Book mode.
- 1 13. A method according to claim 1 wherein said second function includes an
- 2 encryption function resulting from combined use of more than one symmetric key cipher.
- 1 17. A method according to claim 14 wherein said first function includes a
- 2 cryptographic pseudo random generator.
- 1 20. A method according to claim 14 wherein said accessory data strings include two
- 2 parts, one part being derived by the decrypting party in a predetermined fashion from
- 3 available sources prior to decrypting said ith ciphertext segment and the other part not
- 4 being derived by, and therefore being received by, the decrypting party prior to decrypting
- 5 said *i*th ciphertext segment.
- 1 21. A method according to claim 14 wherein said second function includes a
- 2 decryption function of a symmetric key cipher.

- 1 22. A method according to claim 14 wherein said second function includes a
- 2 decryption function of a block cipher operating in a well known mode, such as Electronic
- 3 Code Book mode.
- 1 23. A method according to claim 14 wherein said second function includes a
- 2 decryption function resulting from a combined use of more than one symmetric key cipher.
- 1 27. Apparatus according to claim 24 wherein said means for outputting is adapted for
- 2 outputting the size of the corresponding data segment.
- 1 28. Apparatus according to claim 24 wherein said first function includes a
- 2 cryptographic pseudo random generator.
- 1 31. Apparatus according to claim 24 wherein said accessory data strings are derived
- 2 from various sources.
- 1 34. Apparatus according to claim 24 wherein said second function includes an
- 2 encryption function of a symmetric key cipher.
- 1 35. Apparatus according to claim 24 wherein said second function includes an
- 2 encryption function of a block cipher operating in a well known mode, such as Electronic
- 3 Code Book mode.
- 1 36. Apparatus according to claim 24 wherein said second function includes an
- 2 encryption function resulting from combined use of more than one symmetric key cipher.

55780.01/2085.00200 - 3 -

- 1 40. Apparatus according to claim 37 wherein said first function includes a
- 2 cryptographic pseudo random generator.
- 1 43. Apparatus according to claim 37 wherein said accessory data strings include two
- 2 parts, one part being derived by the decrypting party in a predetermined fashion from
- 3 available sources prior to decrypting said ith ciphertext segment and the other part not
- being derived by, and therefore being received by, the decrypting party prior to decrypting
- 5 said *i*th ciphertext segment.
- 1 44. Apparatus according to claim 37 wherein said second function includes a
- 2 decryption function of a symmetric key cipher.
- 1 45. Apparatus according to claim 37 wherein said second function includes a
- 2 decryption function of a block cipher operating in a well known mode, such as Electronic
- 3 Code Book mode.
- 1 46. Apparatus according to claim 37 wherein said second function includes a
- 2 decryption function resulting from a combined use of more than one symmetric key cipher.

REMARKS

Prior to a first Office action in this matter, the Examiner is requested to enter the above amendments above and consider the accompanying remarks. The amendments were made simply to change the multiple dependent claims to depend on only one other claim and, in no way, narrowed the scope of any claim

Respectfully submitted,

hathan M. Harris

PTO Reg. No. 44,144

CONLEY, ROSE & TAYON

P.O. Box 3267

Houston, TX 77253-3267

(713) 238-8000 (Phone)

(713) 238-8008 (Fax)

ATTORNEY FOR APPLICANTS

MARKED-UP VERSION OF AMENDMENTS

IN THE CLAIMS:

- 1 1. A method of encrypting data suitable for sending to a decrypting party, said
- 2 method including the steps of:
- 3 (a) dividing said data into data segments;
- 4 (b) accepting at least a cryptographic key k shared with the decrypting party;
- 5 (c) for the *i*th data segment (i = 1, 2 ...) to be encrypted, generating the *i*th
- 6 segment key S_i using a first function with said cryptographic key k and some accessory
- 7 data strings as inputs;
- 8 (d) encrypting the *i*th data segment using a second function with S_i as the
- 9 encryption key to form the *i*th ciphertext segment; and
- 10 (e) outputting the *i*th ciphertext segment, and at least a part of said accessory
- data strings for sending data to the decrypting party, and if more data segments are to be
- encrypted, repeating steps (c), (d) and (e).
- 1 2. A method according to claim 1 wherein said accessory data strings include a single
- string V_i derived from the previous value V_{i-1} in a predetermined fashion.
- 1 3. A method according to claim 2 wherein said string vi is derived according to the
- 2 relation $V_i = F(V_{i-1})$, i = 1, 2, ..., wherein F() maps V_{i-1} to V_i and V_o is an initialization value
- 3 made known to the decrypting party.
- 1 4. (Once Amended) A method according to claim 1, 2 or 3 wherein step (e)
- 2 includes outputting the size of the corresponding data segment.

- 1 5. (Once Amended) A method according [to any one of the preceding claims] claim
- 2 <u>1</u> wherein said first function includes a cryptographic pseudo random generator.
- 1 6. A method according to claim 5 wherein said pseudo random generator includes a
- 2 keyed hash function $h(k, V_{i1}, V_{i2}, ..., V_{il})$, wherein k is said cryptographic key, $(V_{i1}, V_{i2}, ..., V_{il})$
- 3 is said accessory data strings and l is a positive integer.
- 1 7. A method according to claim 6 wherein h() is MD5 or SHA.
- 1 8. (Once Amended) A method according to [any one of the preceding claims] claim
- 2 <u>1</u> wherein said accessory data strings are derived from various sources.
- 1 9. A method according to claim 8 wherein said sources include current time and date,
- 2 or previous accessory data strings, or some initialization values, or at least a part of the
- data segments or previous ciphertext segments, or at least a part of previous segment keys.
- 1 10. A method according to claim 1 wherein said accessory data strings include two
- 2 parts, one part being derived by the decrypting party in a predetermined fashion prior to
- 3 decrypting said ith ciphertext segment and the other part not being derived by, and
- 4 therefore being sent to, the decrypting party prior to decrypting said ith ciphertext segment.
- 1 11. (Once Amended) A method according to [any one of the preceding claims] claim
- 2 1 wherein said second function includes an encryption function of a symmetric key cipher.

55780.01/2085.00200 - 7 -

- 1 12. (Once Amended) A method according to [any one of claims 1 to 10] claim 1
- 2 wherein said second function includes an encryption function of a block cipher operating
- 3 in a well known mode, such as Electronic Code Book mode.
- 1 13. (Once Amended) A method according to [any one of claims 1 to 10] claim 1
- 2 wherein said second function includes an encryption function resulting from combined use
- 3 of more than one symmetric key cipher.
- 1 14. A method of decrypting data encrypted by an encrypting party, said method
- 2 including the steps of:
- 3 (a) accepting at least a cryptographic key k being shared with the encrypting
- 4 party;
- 5 (b) for the *i*th ciphertext segment (i = 1, 2, ...,) to be decrypted, generating the
- 6 ith segment key S_i using a first function with said cryptographic key k and some accessory
- 7 data strings as inputs;
- 8 (c) decrypting the *i*th ciphertext segment using a second function with S_i as the
- 9 decryption key;
- 10 (d) outputting the decrypted *i*th ciphertext segment, and if more ciphertext
- segments are to be decrypted, repeating steps (b), (c) and (d).
- 1 15. A method according to claim 14 wherein said accessory data strings include a
- single string V_i derived from the previous value V_{i-1} in a predetermined fashion.

- 1 16. A method according to claim 15 wherein said string V_i is derived according to the
- relation $V_i = F(V_{i-1})$, i = 1, 2, ..., wherein F() maps V_{i-1} to V_i and V_o is an initialization value
- 3 made known to the encrypting party.
- 1 17. (Once Amended) A method according to claim 14[, 15 or 16] wherein said first
- 2 function includes a cryptographic pseudo random generator.
- 1 18. A method according to claim 17 wherein said pseudo random generator includes a
- 2 keyed hash function $h(k, V_{i1}, V_{i2}, ..., V_{il})$, wherein k is said cryptographic key, $(V_{i1}, V_{i2}, ..., V_{il})$
- 3 is said accessory data strings and *l* is a positive integer.
- 1 19. A method according to claim 18 wherein h() is MD5 or SHA.
- 1 20. (Once Amended) A method according to [any one of claims 14 to 19] claim 14
- 2 wherein said accessory data strings include two parts, one part being derived by the
- 3 decrypting party in a predetermined fashion from available sources prior to decrypting said
- 4 ith ciphertext segment and the other part not being derived by, and therefore being received
- by, the decrypting party prior to decrypting said *i*th ciphertext segment.
- 1 21. (Once Amended) A method according to [any one of claims 14 to 20] claim 14
- 2 wherein said second function includes a decryption function of a symmetric key cipher.
- 1 22. (Once Amended) A method according to [any one of claims 14 to 20] claim 14
- 2 wherein said second function includes a decryption function of a block cipher operating in
- 3 a well known mode, such as Electronic Code Book mode.

55780.01/2085.00200 - 9 -

- 1 23. (Once Amended) A method according to [any one of claims 14 to 20] claim 14
- 2 wherein said second function includes a decryption function resulting from a combined use
- 3 of more than one symmetric key cipher.
- 1 24. Apparatus for encrypting data suitable for sending to a decrypting party, said
- 2 apparatus including:
- 3 (a) means for dividing said data into data segments;
- 4 (b) means for accepting at least a cryptographic key k shared with the
- 5 decrypting party;
- 6 (c) means for generating for the *i*th data segment (i = 1, 2, ...,) to be encrypted,
- 7 the *i*th segment, key S_i using a first function with said cryptographic key k and some
- 8 accessory data strings as inputs;
- 9 (d) means for encrypting the *i*th data segment using a second function with S_i as
- 10 the encryption key to form the *i*th ciphertext segment; and
- 11 (e) means for outputting the *i*th ciphertext segment, and at least a part of said
- accessory data strings for sending data to the decrypting party.
- 1 25. Apparatus according to claim 24 wherein said accessory data strings include a
- single string V_i derived from the previous value V_{i-1} in a predetermined fashion.
- 1 26. Apparatus according to claim 25 wherein said string V_i is derived according to the
- 2 relation $V_i = F(V_{i-1})$, i = 1, 2, ..., wherein F() maps V_{i-1} to V_i and V_o is an initialization value
- 3 made known to the decrypting party.

- 1 27. (Once Amended) Apparatus according to claim 24[, 25 or 26] wherein said means
- 2 for outputting is adapted for outputting the size of the corresponding data segment.
- 1 28. (Once Amended) Apparatus according to [any one of claims 24 to 27] claim 24
- 2 wherein said first function includes a cryptographic pseudo random generator.
- 1 29. Apparatus according to claim 28 wherein said pseudo random generator includes a
- 2 keyed hash function $h(k, V_{il}, V_{i2}, ..., V_{il})$, wherein k is said cryptographic key, $(V_{il}, V_{i2}, ..., V_{il})$
- 3 is said accessory data strings and l is a positive integer.
- 1 30. Apparatus according to claim 29 wherein h() is MD5 or SHA.
- 1 31. (Once Amended) Apparatus according to [any one of claims 24 to 29] claim 24
- 2 wherein said accessory data strings are derived from various sources.
- 1 32. Apparatus according to claim 31 wherein said sources include current time and
- 2 date, or previous accessory data strings, or some initialization values, or at least a part of
- 3 the data segments or previous ciphertext segments, or a part of previous segment keys.
- 1 33. Apparatus according to claim 24 wherein said accessory data strings include two
- 2 parts, one part being derived by the decrypting party in a predetermined fashion prior to
- 3 decrypting said ith ciphertext segment and the other part not being derived by, and
- 4 therefore being sent to, the decrypting party prior to decrypting said *i*th ciphertext segment.

- 1 34. (Once Amended) Apparatus according to [any one of claims 24 to 33] claim 24
- 2 wherein said second function includes an encryption function of a symmetric key cipher.
- 1 35. (Once Amended) Apparatus according to [any one of claims 24 to 33] claim 24
- 2 wherein said second function includes an encryption function of a block cipher operating
- 3 in a well known mode, such as Electronic Code Book mode.
- 1 36. (Once Amended) Apparatus according to [any one of claims 24 to 33] claim 24
- 2 wherein said second function includes an encryption function resulting from combined use
- 3 of more than one symmetric key cipher.
- 1 37. Apparatus for decrypting data encrypted by an encrypting party, said apparatus
- 2 including:
- 3 (a) means for accepting at least a cryptographic key k being shared with the
- 4 encrypting party;
- 5 (b) means for generating as inputs for the *i*th ciphertext segment (i = 1, 2, ...,)
- 6 to be decrypted, the *i*th segment key S_i using a first function with said cryptographic key k
- 7 and some accessory data strings;
- 8 (c) means for decrypting the *i*th ciphertext segment using a second function
- 9 with S_i as the decryption key; and
- 10 (d) means for outputting the decrypted *i*th ciphertext segment.
- 1 38. Apparatus according to claim 37 wherein said accessory data strings include a
- single string V_i derived from the previous value V_{i-I} in a predetermined fashion.

- 1 39. Apparatus according to claim 38 wherein said string V_i is derived according to the
- 2 relation $V_i = F(V_{i-1})$, i = 1, 2, ..., wherein F() maps V_{i-1} to V_i and V_o is an initialization value
- 3 made known to the encrypting party.
- 1 40. (Once Amended) Apparatus according to claim 37, 38 or 39 wherein said first
- 2 function includes a cryptographic pseudo random generator.
- 1 41. Apparatus according to claim 40 wherein said pseudo random generator includes a
- 2 keyed hash function $h(k, V_{i1}, V_{i2}, ..., V_{il})$, wherein k is said cryptographic key, $(V_{i1}, V_{i2}, ..., V_{il})$
- 3 is said accessory data strings and l is a positive integer.
- 1 42. Apparatus according to claim 41 wherein h() is MD5 or SHA.
- 1 43. (Once Amended) Apparatus according to [any one of claims 37 to 42] claim 37
- 2 wherein said accessory data strings include two parts, one part being derived by the
- 3 decrypting party in a predetermined fashion from available sources prior to decrypting said
- 4 ith ciphertext segment and the other part not being derived by, and therefore being received
- 5 by, the decrypting party prior to decrypting said *i*th ciphertext segment.
- 1 44. (Once Amended) Apparatus according to [any one of claims 37 to 43] <u>claim 37</u>
- 2 wherein said second function includes a decryption function of a symmetric key cipher.
- 1 45. (Once Amended) Apparatus according to [any one of claims 37 to 43] claim 37
- 2 wherein said second function includes a decryption function of a block cipher operating in
- 3 a well known mode, such as Electronic Code Book mode.

55780.01/2085.00200 - 13 -

- 1 46. (Once Amended) Apparatus according to [any one of claims 37 to 43] claim 37
- 2 wherein said second function includes a decryption function resulting from a combined use
- 3 of more than one symmetric key cipher.



PTO/PCT Rec'd 24 SEP 2001

METHOD AND APPARATUS FOR ENCRYPTING AND DECRYPTING DATA

FIELD OF THE INVENTION

5

The present invention relates to cryptography and in particular to a method and apparatus for encrypting and decrypting digital data for the purpose of protecting or securing its contents.

10

15

20

25

30

BACKGROUND OF THE INVENTION

There exists a need to transfer data confidentially over an open channel or to store such data securely in an unsecure location. Whilst such transfer or storage may be achieved by physical means, it is more effective and/or flexible to use cryptographic means.

In the prior art, to send private communications between two parties, the parties need to share a cryptographic key and use a symmetric-key cipher to encrypt and decrypt data. Various ciphers including block ciphers and stream ciphers have been proposed in the past. A stream cipher handles messages of arbitrary size by ciphering individual elements, such as bits or bytes of data. This avoids the need to accumulate data into a block before ciphering as is necessary in a block cipher. A conventional block cipher requires an accumulation of a certain amount of data or multiple data elements for ciphering to complete. Examples of block ciphers include DES (see ANSI X3.92, "American National Standard for Data Encryption Algorithm (DEA)," American National Standards Institute, 1981), IDEA (see X. Lai, J. Massey, and S. Murphy, "Markov ciphers and differential cryptanalysis," Advances in Cryptology -EUROCRYPT'91 Proceedings, Springer-Verlag, 1991, pp. 17-38), SAFER (see J. Massey. SAFER K-64: One year later. In B. Preneel, editor, Fast Software Encryption - Proceedings of Second International Workshop, LNCS 1008, pages 212-241, Springer Verlag, 1995), and RC5 (see R. Rivest, "The RC5 encryption algorithm," Dr. Dobb's Journal, Vol. 20, No. 1, January 1995, pp. 146 -148). A typical data encryption

speed for these ciphers is several million bits per second (Mb/s) on a Pentium 266 MHz processor.

Due to the pervasiveness of high-speed networking and multimedia communications, the demand for high-speed ciphers is ever increasing. For example, data rates over Asynchronous Data Transfer networks range from several tens of Mb/s to 1 Gb/s. Software implementations of existing block ciphers cannot reach these kinds of data rates.

In general, stream ciphers are much faster than block ciphers. However, stream ciphers are usually not sufficiently analyzed and are perceived to be weaker in security than block ciphers. Many stream ciphers that we believed to be very secure were subsequently broken. The design of secure and efficient high-speed ciphers remains a highly challenging problem.

15

20

Many powerful cryptanalytical methods have been developed during the past decade or so. It may be observed that the success of many of these methods in attacking a cipher depends on the availability of a large quantity of ciphertexts/plaintenxts under a particular encryption key. Normally, the likelihood of successfully attacking a cipher, i.e., discovering the key, diminishes as the amount of available ciphertexts/plaintexts decreases. The present invention, is motivated by the above observation, and provides an improved method and apparatus for data encryption and decryption.

25

30

SUMMARY OF THE INVENTION

The method of the present invention may employ a combination of at least two cryptographic algorithms to achieve relatively high throughput without compromizing security. A first algorithm may be a cryptographic pseudo random sequence (or number) generator with strong security, and a second algorithm may be a cipher capable of high-speed operation, but may be weak in security when used alone. The first algorithm may be used to systematically and periodically generate "segment keys" and the second algorithm may be used to encrypt a data segment or plaintext segment using a segment key. Each data

10

15

20

30

segment may be encrypted using a different segment key. By limiting the sizes of the data segments, an attacker may not have sufficient plaintexts or ciphertexts under a given segment key to carry out meaningful cryptanalysis against the second algorithm. In doing so, the present invention may achieve high throughput in data encryption and decryption without compromizing overall security of the system.

-3-

According to one aspect of the present invention there is provided a method of encrypting data suitable for sending to a decrypting party, said method including the steps of:

- (a) dividing said data into data segments;
- (b) accepting at least a cryptographic key k shared with the decrypting party;
- (c) for the *i*th data segment (i = 1, 2, ...) to be encrypted, generating the *i*th segment key s_i using a first function with said cryptographic key k and some accessory data strings as inputs;
- (d) encrypting the ith data segment using a second function with s_i as the encryption key to form the ith ciphertext segment; and
- (e) outputting the ith ciphertext segment, and at least a part of said accessory data strings for sending data to the decrypting party, and if more data segments are to be encrypted, repeating steps (c), (d) and (e).

The accessory data strings may include a single string v_i derived from the previous value v_{i-1} in a predetermined fashion. The string v_i may be derived according to the relation $v_i = F(v_{i-1})$, i = 1, 2, ..., wherein F() maps v_{i-1} to v_i and v_o is an initialization value made known to the decrypting party.

According to a further aspect of the present invention there is provided a method of decrypting data encrypted by an encrypting party, said method including the steps of:

(a) accepting at least a cryptographic key k being shared with the encrypting party;

15

- (b) for the ith ciphertext segment (i = 1, 2, ...,) to be decrypted, generating the ith segment key s_i using a first function with said cryptographic key k and some accessory data strings as inputs;
- (c) decrypting the *i*th ciphertext segment using a second function with s_i as the decryption key;
- (d) outputting the decrypted *i*th ciphertext segment, and if more ciphertext segments are to be decrypted, repeating steps (b), (c) and (d).
- 10 According to a still further aspect of the present invention there is provided apparatus for encrypting data suitable for sending to a decrypting party, said apparatus including:
 - (a) means for dividing said data into data segments;
 - (b) means for accepting at least a cryptographic key *k* shared with the decrypting party;
 - (c) means for generating for the *i*th data segment (i = 1, 2, ...) to be encrypted, the *i*th segment key s_i using a first function with said cryptographic key k and some accessory data strings as inputs;
 - (d) means for encrypting the ith data segment using a second function with s_i as the encryption key to form the ith ciphertext segment; and
 - (e) means for outputting the ith ciphertext segment, and at least a part of said accessory data strings for sending data to the decrypting party.
- According to a still further aspect of the present invention there is provided apparatus for decrypting data encrypted by an encrypting party, said apparatus including:
 - (a) means for accepting at least a cryptographic key k being shared with the encrypting party;
- (b) means for generating as inputs for the *i*th ciphertext segment (*i* = 1, 2, ...,) to be decrypted, the *i*th segment key s_i using a first function with said cryptographic key k and some accessory data strings;
 - (c) means for decrypting the *i*th ciphertext segment using a second function with s_i as the decryption key; and

15

20

25

30

(d) means for outputting the decrypted ith ciphertext segment.

The apparatus of the present invention may be conveniently embodied by means of a suitably programmed general purpose digital computer. It is well within the capability of persons skilled in the art of programming digital computers to develop software programs for implementing the encrypting/decrypting methods described herein. Alternatively the apparatus may be implemented via dedicated hardware.

DESCRIPTION OF PREFERRED EMBODIMENT

A preferred embodiment of the present invention will now be described with reference to the accompanying drawings wherein:

FIGURE 1 depicts a flowchart of the operation of an illustrative embodiment of the present invention at the data encrypting end of a communication channel; and

FIGURE 2 depicts a flowchart of the operation of an illustrative embodiment of the present invention at the data decrypting end of a communication channel.

FIGURE 1 shows the operation of the present invention at the encrypting end of a communication channel. Data encryption is performed using two cryptographic algorithms, the first being a cryptographic pseudo random sequence generator R() and the second being a high-speed cipher E(), which may be relatively weak in security when used alone. The pseudo random sequence generator accepts two inputs k and v and outputs a pseudo random sequence s = R(k, v). The high-speed cipher accepts a secret key s and a data segment d and produces the ciphertext c = E(s, d). In addition, the illustrative embodiment uses a predetermined function F() to update an initial value, i. e., $v_i = F(v_{i-1})$. It is assumed that the encrypting end and decrypting ends share a secret key k, an initial value v_0 , and the functions F() and R(). Moreover, it is assumed that the decrypting end knows the decrypting algorithm D() corresponding to the encrypting algorithm E().

As shown in FIGURE 1, at step 100, a program at the encrypting end divides the data to be encrypted into segments of equal or unequal sizes: d_1 , d_2 , ..., d_i , In

The first class will the first first the first class that the first firs

10

15

25

30

the former case the last segment may be padded with random data if necessary; while in the latter case, the sizes of the data segments normally need to be known by the decrypting end to facilitate decryption. Furthermore, the program accepts the shared secret key k and the shared initial value v_0 as inputs, and sets the index i = 0.

At 110, the program inspects if there is any data segment available for encryption, and if not, the program terminates. Assuming that there is a data segment available, the program, at 120, increments the index i by 1, gets an updated initial value $v_i = F(v_{i-1})$, generates a segment key $s_i = R(k, v_i)$, and uses the segment key to encrypt the data segment to get the ciphertext segment $c_i = E(s_i, d_i)$ in a manner that is well known to those skilled in the art.

At 130, the program transmits the ciphertext segment, and optionally the size of the corresponding data segment, to the decrypting end. The program then goes back to 110 to see if more data segments need to be encrypted. If so, the preceding process is repeated.

The function F() is used to update the initial value. One example is $v_i = v_{i-1} + 1$ and another example is a cryptographic hash function.

Those skilled in the art will see that the shared secret key is protected by the cryptographic pseudo random generator $R(k, v_i)$. To obtain good security, it is required that R() be secure against all known attacks to the key k. R() is preferably a secure one-way function or one-way hash function in k. That is, given $R(k, v_i)$ and v_i , it should be computationally hard to find k. One example of a pseudo random generator is a keyed one-way hash function $h(k, v_i)$ or $h(k, p, v_i, k)$ where h() is a one-way hash function and where p pads k to a full input block as specified by some hash functions. Examples of one-way hash functions are MD5 and SHA, (refer respectively, R. Rivest, "The MD5 message digest algorithm," IETF RFC 1321, April 1992 and National Institute of Standards and Technology, NIST FIPS PUB 186, "Digital Signature Standard," U.S. Department of Commerce, May 1994). Another example of a cryptographic pseudo random

10

15

20

25

30

generator is a strong encryption algorithm such as IDEA with k as the encryption key, v_i as plaintext, and the ciphertext output as the pseudo random sequence.

In the illustrative embodiment for encryption, the segment key s_i is used by the cipher E() to encrypt only one data segment d_i . This implies that only the corresponding ciphertext segment c_i and in some cases part of the corresponding data segment are available to an attacker to cryptanalyze the cipher. One selection criteria for E() is that it should be capable of operating at a high-speed. Another selection criteria for E() is that given the limited amount of ciphertexts and even part of the corresponding data segment under a segment key, the cipher E() should be capable of resisting all known attacks. As a consequence, there is a tradeoff between the size of the data segment and system throughput; the larger the size of a data segment, the higher the throughput. On the other hand, a larger data segment implies that more ciphertexts or plaintexts under a segment key are available to an attacker to cryptanalyze the cipher E(). Examples of E() are high-speed stream ciphers or block ciphers with fewer rounds of iterations than that when they are used alone. In the latter case, the notation $E(s_i, d_i)$ represents the encryption of data segment d_i using a block cipher even when the size of the data segment d_i is larger than the block size of the underlying block cipher and the encryption may be performed in various modes, such as Electronic Code Book or Cipher Block Chaining Mode.

One specific example of E() is the following high-speed stream cipher. Let N() be a function defined as $N(s,x)=((((x+s_1)\oplus s_2)\times s_3)\oplus s_4)>>>$, where $s=s_1s_2s_3s_4$ (consisting of four 32-bit strings) is a 128 bit secret key, x is a 32-bit string, \oplus is the bit-wise exclusive-or, + and \times are mod 2^{32} addition and multiplication, and >>> is to reverse a 32 bit string into opposite ranking. Let $b_1b_2 \wedge b_m \wedge$ be the data to be encrypted which is a concatenation of 32 bit strings, the corresponding ciphertexts are given by $d_1=b_1 \oplus N(s,N(s,N(s,d_{i-1})\oplus b_{i-1})\oplus d_{i-2})$, where the initial values d_{-1} , d_{-2} , d_{-3} can be set to s_2,s_3,s_4 .

Another specific example of E() is Serpent with a reduced number of rounds. Serpent is a block cipher with 128 bit block length, variable key lengths, and 32

rounds of operations (see R. Anderson, E. Biham, and L. Knudsen, "Serpent: A Proposal for the Advanced Encryption Standard", http://www.cl.cam.ac.uk/~ria14/serpent.html). Its inventors showed that to attack 6 round Serpent successfully, it would require 2^{56} and 2^{116} plaintext blocks using linear and differential cryptanalysis, respectively. Hence, if a 6 round Serpent is used as E() to encrypt data, it should resist both linear and differential cryptanalysis as long as the data segment size is less than 2^{56} 128 bit blocks. At the same time, this E() is about 5 times faster than the 32 round Serpent.

- FIGURE 2 depicts a flowchart of the operation of the present invention at the data decrypting end of a communication channel. As shown in FIGURE 2, at step 200, a program at the decrypting end accepts the shared secret key k and the shared initial value v_0 as inputs, and sets the index i = 0.
- The program then checks at 210 to see if there is any ciphertext segment available for decryption and if not, the program halts its operation. Assuming that a ciphertext segment is received, the program, at 220, increments the index *i* by 1, updates the initial value $v_i = F(v_{i-1})$, computes a segment key $s_i = R(k, v_i)$, and uses the segment key to decrypt the ciphertext segment to get the data segment $d_i = D(s_i, c_i)$ in a fashion that is well known in the art.

As shown at 230, the program preferably outputs the data segment and then goes back to 210 to see if there is more ciphertext segment available for decryption. If so, the preceding steps are repeated.

25

30

The embodiment described above is merely one illustrative example of realizing the present invention; there can be many variants of this. For example, it is well within the capability of persons skilled in the art to suggest alternative ways of generating segment keys using a pseudo random generator, where the current segment key may depend not only on the cryptographic key k, but also on other variables such as part of the plaintext, part of the ciphertext, a time stamp, and previous segment keys.

Finally, it is to be understood that various alterations, modifications and/or additions may be introduced into the constructions and arrangements of parts previously described without departing from the spirit or ambit of the present invention.

15

25

-10-

CLAIMS

- A method of encrypting data suitable for sending to a decrypting party, said
 method including the steps of:
 - (a) dividing said data into data segments;
 - (b) accepting at least a cryptographic key *k* shared with the decrypting party;
 - (c) for the *i*th data segment (i = 1, 2, ...) to be encrypted, generating the *i*th segment key s_i using a first function with said cryptographic key k and some accessory data strings as inputs;
 - (d) encrypting the *i*th data segment using a second function with s_i as the encryption key to form the *i*th ciphertext segment; and
 - (e) outputting the ith ciphertext segment, and at least a part of said accessory data strings for sending data to the decrypting party, and if more data segments are to be encrypted, repeating steps (c), (d) and (e).
- A method according to claim 1 wherein said accessory data strings include
 a single string v_i derived from the previous value v_{i-1} in a predetermined fashion.
 - 3. A method according to claim 2 wherein said string v_i is derived according to the relation $v_i = F(v_{i-1})$, i = 1, 2, ..., wherein F() maps v_{i-1} to v_i and v_o is an initialization value made known to the decrypting party.
 - 4. A method according to claim 1, 2 or 3 wherein step (e) includes outputting the size of the corresponding data segment.
- 5. A method according to any one of the preceding claims wherein said first30 function includes a cryptographic pseudo random generator.
 - 6. A method according to claim 5 wherein said pseudo random generator includes a keyed hash function $h(k, v_{i1}, v_{i2}, ..., v_{il})$, wherein k is said cryptographic key, $(v_{i1}, v_{i2}, ..., v_{il})$ is said accessory data strings and l is a positive integer.

15

- 7. A method according to claim 6 wherein h() is MD5 or SHA.
- 8. A method according to any one of the preceding claims wherein said
 5 accessory data strings are derived from various sources.
 - 9. A method according to claim 8 wherein said sources include current time and date, or previous accessory data strings, or some initialization values, or at least a part of the data segments or previous ciphertext segments, or at least a part of previous segment keys.
 - 10. A method according to claim 1 wherein said accessory data strings include two parts, one part being derived by the decrypting party in a predetermined fashion prior to decrypting said ith ciphertext segment and the other part not being derived by, and therefore being sent to, the decrypting party prior to decrypting said ith ciphertext segment.
 - 11. A method according to any one of the preceding claims wherein said second function includes an encryption function of a symmetric key cipher.
 - 12. A method according to any one of claims 1 to 10 wherein said second function includes an encryption function of a block cipher operating in a well known mode, such as Electronic Code Book mode.
- 25 13. A method according to any one of claims 1 to 10 wherein said second function includes an encryption function resulting from combined use of more than one symmetric key cipher.
- 14. A method of decrypting data encrypted by an encrypting party, said30 method including the steps of:
 - (a) accepting at least a cryptographic key k being shared with the encrypting party;

20

- (b) for the *i*th ciphertext segment (i = 1, 2, ...) to be decrypted, generating the *i*th segment key s_i using a first function with said cryptographic key k and some accessory data strings as inputs;
- (c) decrypting the *i*th ciphertext segment using a second function with s_i as the decryption key;
- (d) outputting the decrypted ith ciphertext segment, and if more ciphertext segments are to be decrypted, repeating steps (b), (c) and (d).
- 10 15. A method according to claim 14 wherein said accessory data strings include a single string v_i derived from the previous value v_{i-1} in a predetermined fashion.
- 16. A method according to claim 15 wherein said string v_i is derived according to the relation $v_i = F(v_{i-1})$, i = 1, 2, ..., wherein F() maps v_{i-1} to v_i and v_o is an initialization value made known to the encrypting party.
 - 17. A method according to claim 14, 15 or 16 wherein said first function includes a cryptographic pseudo random generator.
 - 18. A method according to claim 17 wherein said pseudo random generator includes a keyed hash function $h(k, v_{i1}, v_{i2}, ..., v_{il})$, wherein k is said cryptographic key, $(v_{i1}, v_{i2}, ..., v_{il})$ is said accessory data strings and l is a positive integer.
- 25 19. A method according to claim 18 wherein h() is MD5 or SHA.
 - 20. A method according to any one of claims 14 to 19 wherein said accessory data strings include two parts, one part being derived by the decrypting party in a predetermined fashion from available sources prior to decrypting said ith ciphertext segment and the other part not being derived by, and therefore being received by, the decrypting party prior to decrypting said ith ciphertext segment.
 - 21. A method according to any one of claims 14 to 20 wherein said second function includes a decryption function of a symmetric key cipher.

15

- 22. A method according to any one of claims 14 to 20 wherein said second function includes a decryption function of a block cipher operating in a well known mode, such as Electronic Code Book mode.
- 23. A method according to any one of claims 14 to 20 wherein said second function includes a decryption function resulting from a combined use of more than one symmetric key cipher.
- 10 24. Apparatus for encrypting data suitable for sending to a decrypting party, said apparatus including:
 - (a) means for dividing said data into data segments;
 - (b) means for accepting at least a cryptographic key *k* shared with the decrypting party;
 - (c) means for generating for the *i*th data segment (i = 1, 2, ...) to be encrypted, the *i*th segment key s_i using a first function with said cryptographic key k and some accessory data strings as inputs;
 - (d) means for encrypting the ith data segment using a second function with s_i as the encryption key to form the ith ciphertext segment; and
- 20 (e) means for outputting the ith ciphertext segment, and at least a part of said accessory data strings for sending data to the decrypting party.
- 25. Apparatus according to claim 24 wherein said accessory data strings
 25 include a single string v_i derived from the previous value v_{i-1} in a predetermined fashion.
 - 26. Apparatus according to claim 25 wherein said string v_i is derived according to the relation $v_i = F(v_{i-1})$, i = 1, 2, ..., wherein F() maps v_{i-1} to v_i and v_o is an initialization value made known to the decrypting party.
 - 27. Apparatus according to claim 24, 25 or 26 wherein said means for outputting is adapted for outputting the size of the corresponding data segment.

20

- 28. Apparatus according to any one of claims 24 to 27 wherein said first function includes a cryptographic pseudo random generator.
- 29. Apparatus according to claim 28 wherein said pseudo random generator includes a keyed hash function $h(k, v_{i1}, v_{i2}, ..., v_{ii})$, wherein k is said cryptographic key, $(v_{i1}, v_{i2}, ..., v_{ii})$ is said accessory data strings and l is a positive integer.
 - 30. Apparatus according to claim 29 wherein h() is MD5 or SHA.
- 10 31. Apparatus according to any one of claims 24 to 29 wherein said accessory data strings are derived from various sources.
 - 32. Apparatus according to claim 31 wherein said sources include current time and date, or previous accessory data strings, or some initialization values, or at least a part of the data segments or previous ciphertext segments, or a part of previous segment keys.
 - 33. Apparatus according to claim 24 wherein said accessory data strings include two parts, one part being derived by the decrypting party in a predetermined fashion prior to decrypting said ith ciphertext segment and the other part not being derived by, and therefore being sent to, the decrypting party prior to decrypting said ith ciphertext segment.
- 34. Apparatus according to any one of claims 24 to 33 wherein said second function includes an encryption function of a symmetric key cipher.
 - 35. Apparatus according to any one of claims 24 to 33 wherein said second function includes an encryption function of a block cipher operating in a well known mode, such as Electronic Code Book mode.
 - 36. Apparatus according to any one of claims 24 to 33 wherein said second function includes an encryption function resulting from combined use of more than one symmetric key cipher.

15

- 37. Apparatus for decrypting data encrypted by an encrypting party, said apparatus including:
 - (a) means for accepting at least a cryptographic key k being shared with the encrypting party;
 - (b) means for generating as inputs for the ith ciphertext segment (i = 1, 2, ...,) to be decrypted, the ith segment key s_i using a first function with said cryptographic key k and some accessory data strings;
 - (c) means for decrypting the *i*th ciphertext segment using a second function with s_i as the decryption key; and
- 10 (d) means for outputting the decrypted ith ciphertext segment.
 - 38. Apparatus according to claim 37 wherein said accessory data strings include a single string v_i derived from the previous value v_{i-1} in a predetermined fashion.
 - 39. Apparatus according to claim 38 wherein said string v_i is derived according to the relation $v_i = F(v_{i-1})$, i = 1, 2, ..., wherein F() maps v_{i-1} to v_i and v_o is an initialization value made known to the encrypting party.
- 40. Apparatus according to claim 37, 38 or 39 wherein said first function includes a cryptographic pseudo random generator.
 - 41. Apparatus according to claim 40 wherein said pseudo random generator includes a keyed hash function $h(k, v_{i1}, v_{i2}, ..., v_{il})$, wherein k is said cryptographic key, $(v_{i1}, v_{i2}, ..., v_{il})$ is said accessory data strings and l is a positive integer.
 - 42. Apparatus according to claim 41 wherein h() is MD5 or SHA.
- 43. Apparatus according to any one of claims 37 to 42 wherein said accessory data strings include two parts, one part being derived by the decrypting party in a predetermined fashion from available sources prior to decrypting said ith ciphertext segment and the other part not being derived by, and therefore being received by, the decrypting party prior to decrypting said ith ciphertext segment.

- 44. Apparatus according to any one of claims 37 to 43 wherein said second function includes a decryption function of a symmetric key cipher.
- 45. Apparatus according to any one of claims 37 to 43 wherein said second
 function includes a decryption function of a block cipher operating in a well known mode, such as Electronic Code Book mode.
- 46. Apparatus according to any one of claims 37 to 43 wherein said second function includes a decryption function resulting from a combined use of more
 10 than one symmetric key cipher.

1/2 DRAWINGS




FIGURE 1



2/2




FIGURE 2

F.
45
tu
1 1
project projec
*
E
me in the
i.s.

the specification of which ☐ is attached hereto

was filed on (MM/DD/YYYY)

Please type a plus sign (+) ınside this box	\rightarrow	+		
---	---------------	---	--	--

03/22/1999

Express Mail Label No.EL915360557US

as United States Application Number or PCT International

(if applicable).

PTO/SB/01 (10-00)

Approved for use through 10/31/2002. OMB 0651-0032

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number

	Attorney Docket Numb	er 2085-00 1 00				
DECLARATION FOR UTILITY OR DESIGN	First Named Inventor	BAO Feng				
PATENT APPLICATION	COMPLETE IF KNOWN					
(37 CFR 1.63)	Application Number	NOT YET / ASSIGNED				
	Filing Date	CONCURRENTLY HEREWITH				
✓ Declaration ☐ Declaration Submitted OR Submitted after Initial	Group Art Unit	UNKNOWN				
with Initial Filing (surcharge (37 CFR 1.16 (e)) required)	Examiner Name	UNKNOWN				
		•				
As a below named inventor, I hereby declare that:						
My residence, mailing address, and citizenship are as stated b	elow next to my name.					
I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:						
Method And Apparatus For Encrypting And Decrypting Data						
(Title o	f the Invention)					

Application Number PCT/SG99	9/00020 and was a	mended on (MM/DD/YY	YY)	(if applicable).	•				
I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.									
I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56, including for continuation-in-part applications, material information which became available between the filing date of the prior application and the national or PCT international filing date of the continuation-in-part application.									
certificate, or 365(a) of any PCT i America, listed below and have	I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or any PCT international application having a filing date before that of the application on which priority is claimed.								
Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached? YES NO	?				
-			000						
Additional foreign application i	numbers are listed on a	supplemental priority da	ta sheet PTO/SB	/02B attached hereto:					
I hereby claim the benefit under	35 U.S.C. 119(e) of an	y United States provision	nal application(s) l	isted below.					
Application Number(s)	Filing Date	e (MM/DD/YYYY)	numbers suppleme	al provisional application are listed on a ental priority data sheet 02B attached hereto.					

[Page 1 of 2]
Burden Hour Statement: This form is estimated to take 21 minutes to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time—you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Hall Alex with the first first first first form the first form for first from the

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it display a valid OMB control number.

POWER OF ATTORNEY OR AUTHORIZATION OF AGENT

Application Number	NOT YET ASSIGNED
Filing Date	CONCURRENTLY HEREWITH
First Named Inventor	BAO Feng
Group Art Unit	UNKNOWN
Examiner Name	UNKNOWN
Attorney Docket Number	2085-00200

I hereby appoi	nt: ners at Customer Number	23505	¬	Place Customer		
OR	iers at Custoffier Hailibei			Number Bar Code Label here		
	er(s) named below:					
	Name			ration Number		
David	A. Rose		26,223			
	ory L. Maag		32,363			
	ael F. Heim		32,702			
Jonath	nan M. Harris		44,144			
as my/our attorr business in the	ney(s) or agent(s) to prosect United States Patent and T	ute the application in rademark Office cor	dentified above	e, and to transact all vith.		
	he correspondence address mentioned Customer Numb		ified applicatio	on to:		
Firm or	Conely, Rose & Tay	on, P.C.				
Individual Na	ime	,			-	
Address	P.O. Box 3267					
Address	Houston		State TX	Zip 77253-3267		
City Country	United States of Ame		Ciaio	1 Zip = 0 207		
Telephone	(713) 238 8000		Fax (713) 238	3 8008		
I am the: Applicant/Inventor. Assignee of record of the entire interest. See 37 CFR 3.71. Statement under 37 CFR 3.73(b) is enclosed. (Form PTO/SB/96).						
	SIGNATURE of	Applicant or Assigne	e of Record			
Name	DENG Huijie, Robert					
Signature	Relay Dus		W0.5			
Date	4/09/2001					
NOTE: Signatures of all forms if more than one s	I the inventors or assignees of recosignature is required, see below*.	ord of the entire interest	or their representa	ative(s) are required. Submit multiple		
✓ *Total of ONE (1)						
		-				

Please type a plus sign	(+) inside this box	$\longrightarrow\hspace{-3mm}$	+

Express Mail Label No. EL915360557US

PTO/SB/81 (10-00)

Approved for use through 10/31/2002. OMB 0651-0035

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it display a valid OMB control number.

POWER OF ATTORNEY OR AUTHORIZATION OF AGENT

Application Number	NOT YET ASSIGNED
Filing Date	CONCURRENTLY HEREWITH
First Named Inventor	BAO Feng
Group Art Unit	UN KNOWN
Examiner Name	UNKNOWN
Attorney Docket Number	2085-00200

I hereby appoint:		Γ						
Practitioners at 0	Customer Number 23505	□	Place Customer Number Bar Code Label here					
Practitioner(s) named below:								
Name Registration Number								
David A. Rose		26,223						
Gregory L. M		32,363						
Michael F. He		32,702						
Jonathan M. I	larris	44,144						
	r agent(s) to prosecute the application ic States Patent and Trademark Office con							
The above-mention OR	Please change the correspondence address for the above-identified application to: The above-mentioned Customer Number. OR							
Firm or Individual Name	Conely, Rose & Tayon, P.C.							
Address	P.O. Box 3267	····						
Address		l max						
City		State TX	Zip 77253-3267					
Country	United States of America	(712) 229 9	000					
Telephone	(713) 238 8000	ax (713) 238 8	008					
I am the: Applicant/Inventor.								
	ord of the entire interest. See 37 CFR 3.7 37 CFR 3.73(b) is enclosed. (Form PT							
	SIGNATURE of Applicant or Assigne	e of Record						
Name BAO F	eng							
Signature ×	18							
Date × 04	109/2001							
NOTE: Signatures of all the inver forms if more than one signature	tors or assignees of record of the entire interest of is required, see below*.	r their representative	e(s) are required. Submit multiple					
✓ *Total of Three (3) for	m is submitted.							
urden Hour Statement: This form is not	inneted to take 2 millions to consider. They will come don							

Burden Hour Statement: This form is estimated to take 3 minutes to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231

PTO/SB/01 (10-00)

Approved for use through 10/31/2002. OMB 0651-0032

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION — Utility or Design Patent Application

ĺ		ustomer Numl Bar Code La		23505	5	OR 🗌	Correspondence address bel	ow	
	Name								
	Address		<u>-</u>						
	Address			40					
_	City				State		ZIP		
	Country	Т	elephone	•			Fax		
Mr. An An Sold South South	I hereby declare that all statements mad are believed to be true; and further that made are punishable by fine or imprison validity of the application or any patent is:	these statem ment. or both	ients wer i. under 1	e made wil	ih the ki	nowledde that Willi	ui taise statements and the	like so	
often from	NAME OF SOLE OR FIRST INVENTOR:			☐ A petition has been filed for this unsigned invent					
	Given Name Feng (first and middle [if any])				Family or Surr	Name BAO			
a Ci	Inventor's Signature						04/09/20	0	
Tank Ann wall that	Residence: City Singapore	SGX		State		Country SG	Citizenship P.R.China	ι	
	Mailing Address 37 West Coast Park	37 West Coast Park, #04-06, Parkview Condo							
ļ.	Mailing Address								
	City Singapore	State			ZIP ¹	27653	Country Singapore		
	NAME OF SECOND INVENTOR:				A peti	tion has been fi	led for this unsigned inv	entor	
	Given Name (first and middle [if any]) Huijie, Robe	rt			Family or Suri				
), 1	Inventor's K.M. Rung Residence: City Singapore						Date 4/09/201	7/	
	Residence: City Singapore	6X		State		Country SG	Citizenship Singapore	;	
	Mailing Address 2 Namly Rise								
	Mailing Address								
	City Singapore	State			ZIP 26	57110	Country Singapore		
	Additional inventors are being named	on thes	suppleme	ntal Additio	nal Inve	ntor(s) sheet(s) PT	O/SB/02A attached hereto.		